

Copyright © 2023 Konnectronix, Inc. All Rights Reserved. Konnectronix TM is a trademark of Konnectronix, Inc.

The products and product platforms described herein may be covered by one or more US and/or foreign patents or patents pending. For a complete listing, visit konnectronix.com/legal.html.

2.5 INCH

SPECIFICATIONS:

Electrical

5V @ 2.2A (based on standard cable configuration) Characteristic Impedence Matching Available

Environmental

-20°C to 85°C Operating Temperature

Material

ABS (Black)

(Custom Colors Available in Volume)

Physical

Dimensions: 2.5" Diameter x 1.75" High Retractable Cable Length: Up to 45 Inches*

Cable Type: Customer Specified Connectors: Customer Specified

Mounting Options: Flush Using Inserts Brackets Available

Optional Internal Ratchet System

Certifications

Custom/Specialty Certifications, Including ROHS Compliance, Upon Request

PATENTED TECHNOLOGY

Depending on product configuration, the 2.5 INCH Platform may be covered by one or more patents. For a complete listing, please visit www.konnectronix.com/legal.html

Retractable lengths depend on cable construction (e.g. number of conductors and insulation type)

CORD F	REEL SOLUT	FIONS F Stationary Length	OR VARYING Number of Conductors	NEEDS Max Retractable Length
2.5 INCH	24 and below	any	1-8	45 inches
	Platform specifications depend on factors like cable construction, number of conductors and insulation type.			
OTHER PLATFORMS AVAILABLE				
5 INCH	24 and below	any	1-8	25 feet
	Platform specifications depend on factors like cable construction, number of conductors and insulation type.			
 7 INCH	14 and below	any	1-8	15 feet
•	Platform specifications depend on factors like cable construction, number of conductors and insulation type.			
7 MAXX	14 and below	any	1-8	25 feet
	Platform specifications depend on factors like cable construction, number of conductors and insulation type.			



847-672-8685 inquiry@konnectronix.com